



Product information MACH102-8TP-FR

Industrial Ethernet:Workgroup Switches:Fast-/Gigabit Ethernet Workgroup Switches, 10/24 ports :MACH102-8TP-FR

<http://www.e-catalog.beldensolutions.com/link/57078-24455-49848-85612-40979/en/conf/uistate>

Name	MACH102-8TP-FR
	
	10 port Fast Ethernet/Gigabit Ethernet Industrial Workgroup Switch (2 x GE, 8 x FE), managed, Software Layer 2 Professional, Store-and-Forward-Switching, fanless Design, redundant power supply
Delivery informations	
Availability	available
Product description	
Description	10 port Fast Ethernet/Gigabit Ethernet Industrial Workgroup Switch (2 x GE, 8 x FE), managed, Software Layer 2 Professional, Store-and-Forward-Switching, fanless Design, redundant power supply
Port type and quantity	10 ports in total; 8x (10/100 BASE-TX, RJ45) and 2 Gigabit Combo ports
Type	MACH102-8TP-FR
Order No.	943 969-301
More Interfaces	
Power supply/signaling contact	1 x plug-in terminal block, 2-pin, output manual or automatic switchable (max. 1 A, 24 V DC bzw. 24 V AC)
V.24 interface	1 x RJ11 socket, serial interface for device configuration
USB interface	1 x to connect auto-configuration adapter ACA21-USB
Network size - length of cable	
Twisted pair (TP)	0 - 100 m
Multimode fiber (MM) 50/125 µm	Fast Ethernet: cf. SFP LWL module M-FAST SFP-MM/LC; Gigabit Ethernet: cf. SFP LWL module M-SFP-SX/LC and M-SFP-LX/LC
Multimode fiber (MM) 62.5/125 µm	Fast Ethernet: cf. SFP LWL module M-FAST SFP-MM/LC; Gigabit Ethernet: cf. SFP LWL module M-SFP-SX/LC and M-SFP-LX/LC
Single mode fiber (SM) 9/125 µm	Fast Ethernet: cf. SFP LWL module M-FAST SFP-SM/LC and M-FAST SFP-SM+/LC; Gigabit Ethernet: cf. SFP LWL module M-SFP-LX/LC
Single mode fiber (LH) 9/125 µm (long haul transceiver)	Fast Ethernet: cf. SFP LWL modul M-FAST SFP-LH/LC; Gigabit Ethernet: cf. SFP LWL modul M-SFP-LH/LC and M-SFP-LH+/LC
Network size - cascading	
Line - / star topology	any
Ring structure (HIPER-Ring) quantity switches	50 (reconfiguration time < 0,3 sec.)
Power requirements	
Operating voltage	100 - 240 VAC, 47 - 63 Hz (redundant)
Power output in Btu (IT) h	44
Rated current	0.4 - 0.2 A
Power consumption	13 W
Software	
Management	serial Interface, web interface, SNMP V1/V2, HViSion file transfer SW HTTP/TFTP, LLDP-MED
Diagnostics	LEDs, log-file, syslog, relay contact, RMON, port mirroring 1:1 and n:1, egress/ingress traffic configurable, topology discovery 802.1AB, cable tester (TX), address conflict detection, network error detection, SFP diagnostic [temperature, optical input and output power (µW and dBm)], Trap for configuration saving and changing, duplex mismatch detection, disable learning, Port Monitor
Configuration	Comand line interface (CLI), TELNET, BootP, DHCP, DHCP option 82, HIDiscovery, easy device exchange with auto-configuration adapter ACA21-USB (automatic software and/or configuration upload), automatic script load from ACA21, integrated DHCP server per port, DHCP relay, automatic invalid configuration undo, Offline Configuration, SFP Whitelist, ARC automatic ring configuration (MRP), automatic port shutdown (link flapping), configuration signature (water marking), overload detection
Security	ACL/QoS, ACL Layer 4 fragment support, Port Security (IP und MAC) with multiple addresses (MAC 50 per port), SNMP V3, SSH, Authentication (IEEE802.1x), 802.1x Multi Client Authentication, Guest VLAN and Unauthenticated VLAN, Port based Radius VLAN assignment, MAC notification
Redundancy functions	HIPER-Ring, MRP, MSTP, RSTP - IEEE802.1D-2004, MRP and RSTP gleichzeitig, Link Aggregation, redundant 100 - 240 VAC power supply
Filter	QoS 8 classes, prioritisation (IEEE 802.1D/p), VLAN (IEEE 802.1Q), Voice VLAN, shared VLAN learning, Q-in-Q double VLAN tagging, multicast IGMP v1/v2/v3, (snoothing/querier), multicast detection unknown multicast, broadcast-, unicast-, multicast limiter, fast aging, GMRP IEEE 802.1D, Jumbo Frame Support, Industrial Profiles, EtherNet/IP und PROFINET (2.2 PDEV, GSDML Stand-alone generator, automatic device exchange) profiles included, configuration and diagnostic via automation, software tools like e.g. STEP7, oder Control Logix IEC61850 protocol (MMS Server, Switch Model)



Industrial Ethernet: Workgroup Switches: Fast-/Gigabit Ethernet Workgroup Switches, 10/24 ports :MACH102-8TP-FR

<http://www.e-catalog.beldensolutions.com/link/57078-24455-49848-85612-40979/en/conf/ui/state>

Industrial Profiles	EtherNet/IP, PROFINET, configuration and diagnostic via automation software tools like e.g. STEP7, or Control Logix
Time synchronisation	PTP IEEE 1588 v1/v2 Boundary and Transparent Clock hardware time stamping with accuracies of 30ns, SNTP server, realtime clock with energy buffer
Flow control	Flow Control 802.3x, Port Priority 802.1D/p, Priority (TOS/DIFFSERV), Prio (MAC/IP), Prio Mapping (TOS Layer2), Traffic Shaping (Unicast, Multicast, Broadcast) Ingress / Egress
Ambient conditions	
Operating temperature	0° - +50°C
Storage/transport temperature	-20° - +85°C
Relative humidity (non-condensing)	10% to 95%
MTBF	18,06 years (MIL-HDBK-217F Gb 25°C)
Mechanical construction	
Dimensions (W x H x D)	448 x 44 x 310 (without fixing bracket)
Mounting	19" control cabinet
Weight	3.85 kg
Protection class	IP20
EMC interference immunity	
EN 61000-4-2 electrostatic discharge (ESD)	4 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80 - 2700 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 4 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 4 kV data line
EN 61000-4-6 conducted immunity	10 V (150 kHz - 80 MHz)
EMC emitted immunity	
FCC CFR47 Part 15	FCC 47 CFR Part 15 Class A
EN 55022	EN 55022 Class A
Approvals	
Safety of industrial control equipment	cUL 508
Safety of information technology equipment	cUL 60950-1
Scope of delivery and accessories	
Scope of delivery	MACH100 device, terminal block for signal contact, 2 brackets with fasteningscrews (pre-assembled), housing feet - stick-on, non-heating appliance cable - Euro model, CD-ROM with user manual, installation user manual
Accessories to order separately	Fast Ethernet SFP modules, Gigabit Ethernet SFP modules, autoConfiguration Adapter ACA21-USB, terminal cable, Industrial Hivision Network Management software

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.



Product information MACH102-8TP-F

Industrial Ethernet:Workgroup Switches:Fast-/Gigabit Ethernet Workgroup Switches, 10/24 ports :MACH102-8TP-F

<http://www.e-catalog.beldensolutions.com/link/57078-24455-49848-85612-40980/en/conf/uistate>

Name	MACH102-8TP-F
	
	10 port Fast Ethernet/Gigabit Ethernet Industrial Workgroup Switch (2 x GE, 8 x FE), managed, Software Layer 2 Professional, Store-and-Forward-Switching, fanless Design
Delivery informations	
Availability	available
Product description	
Description	10 port Fast Ethernet/Gigabit Ethernet Industrial Workgroup Switch (2 x GE, 8 x FE), managed, Software Layer 2 Professional, Store-and-Forward-Switching, fanless Design
Port type and quantity	10 ports in total; 8x (10/100 BASE-TX, RJ45) and 2 Gigabit Combo ports
Type	MACH102-8TP-F
Order No.	943 969-201
More Interfaces	
Power supply/signaling contact	1 x plug-in terminal block, 2-pin, output manual or automatic switchable (max. 1 A, 24 V DC bzw. 24 V AC)
V.24 interface	1 x RJ11 socket, serial interface for device configuration
USB interface	1 x to connect auto-configuration adapter ACA21-USB
Network size - length of cable	
Twisted pair (TP)	0 - 100m
Multimode fiber (MM) 50/125 µm	Fast Ethernet: cf. SFP LWL module M-FAST SFP-MM/LC; Gigabit Ethernet: cf. SFP LWL module M-SFP-SX/LC and M-SFP-LX/LC
Multimode fiber (MM) 62.5/125 µm	Fast Ethernet: cf. SFP LWL module M-FAST SFP-MM/LC; Gigabit Ethernet: cf. SFP LWL module M-SFP-SX/LC and M-SFP-LX/LC
Single mode fiber (SM) 9/125 µm	Fast Ethernet: cf. SFP LWL module M-FAST SFP-SM/LC and M-FAST SFP-SM+/LC; Gigabit Ethernet: cf. SFP LWL module M-SFP-LX/LC
Single mode fiber (LH) 9/125 µm (long haul transceiver)	Fast Ethernet: cf. SFP LWL modul M-FAST SFP-LH/LC; Gigabit Ethernet: cf. SFP LWL modul M-SFP-LH/LC and M-SFP-LH+/LC
Network size - cascading	
Line - / star topology	any
Ring structure (HIPER-Ring) quantity switches	50 (reconfiguration time < 0,3 sec.)
Power requirements	
Operating voltage	100 - 240 VAC, 47 - 63 Hz
Power output in Btu (IT) h	41
Rated current	0.4 - 0.2 A
Power consumption	12 W
Software	
Management	serial Interface, web interface, SNMP V1/V2, HiVision file transfer SW HTTP/TFTP, LLDP-MED
Diagnostics	LEDs, log-file, syslog, relay contact, RMON, port mirroring 1:1 and n:1, egress/ingress traffic configurable, topology discovery 802.1AB, cable tester (TX), address conflict detection, network error detection, SFP diagnostic [temperature, optical input and output power (µW and dBm)], Trap for configuration saving and changing, duplex mismatch detection, disable learning, Port Monitor
Configuration	Comand line interface (CLI), TELNET, BootP, DHCP, DHCP option 82, HiDiscovery, easy device exchange with auto-configuration adapter ACA21-USB (automatic software and/or configuration upload), automatic script load from ACA21, integrated DHCP server per port, DHCP relay, automatic invalid configuration undo, Offline Configuration, SFP Whitelist, ARC automatic ring configuration (MRP), automatic port shutdown (link flapping), configuration signature (water marking), overload detection
Security	ACL/QoS, ACL Layer 4 fragment support, Port Security (IP und MAC) with multiple addresses (MAC 50 per port), SNMP V3, SSH, Authentication (IEEE802.1x), 802.1x Multi Client Authentication, Guest VLAN and Unauthenticated VLAN, Port based Radius VLAN assignment, MAC notification
Redundancy functions	HIPER-Ring, MRP, MSTP, RSTP - IEEE802.1D-2004, MRP and RSTP gleichzeitig, Link Aggregation
Filter	QoS 8 classes, prioritisation (IEEE 802.1D/p), VLAN (IEEE 802.1Q), Voice VLAN, shared VLAN learning, Q-in-Q double VLAN tagging, multicast IGMP v1/v2/v3, (snoothing/querier), multicast detection unknown multicast, broadcast-, unicast-, multicast limiter, fast aging, GMRP IEEE 802.1D, Jumbo Frame Support, Industrial Profiles, EtherNet/IP und PROFINET (2.2 PDEV, GSDML Stand-alone generator, automatic device exchange) profiles included, configuration and diagnostic via automation, software tools like e.g. STEP7, oder Control Logix IEC61850 protocol (MMS Server, Switch Model)



Industrial Ethernet:Workgroup Switches:Fast-/Gigabit Ethernet Workgroup Switches, 10/24 ports :MACH102-8TP-F

<http://www.e-catalog.beldensolutions.com/link/57078-24455-49848-85612-40980/en/conf/ui/state>

Industrial Profiles	EtherNet/IP, PROFINET, configuration and diagnostic via automation software tools like e.g. STEP7, or Control Logix
Time synchronisation	PTP IEEE 1588 v1/v2 Boundary and Transparent Clock hardware time stamping with accuracies of 30ns, SNTP server, realtime clock with energy buffer
Flow control	Flow Control 802.3x, Port Priority 802.1D/p, Priority (TOS/DIFFSERV), Prio (MAC/IP), Prio Mapping (TOS Layer2), Traffic Shaping (Unicast, Multicast, Broadcast) Ingress / Egress
Ambient conditions	
Operating temperature	0° - +50°C
Storage/transport temperature	-20° - +85°C
Relative humidity (non-condensing)	10% to 95%
MTBF	15.67 years (MIL-HDBK-217F Gb 25°C)
Mechanical construction	
Dimensions (W x H x D)	448 x 44 x 310 (without fixing bracket)
Mounting	19" control cabinet
Weight	3.60 kg
Protection class	IP20
EMC interference immunity	
EN 61000-4-2 electrostatic discharge (ESD)	4 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80 - 2700 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 4 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 4 kV data line
EN 61000-4-6 conducted immunity	10 V (150 kHz - 80 MHz)
EMC emitted immunity	
FCC CFR47 Part 15	FCC 47 CFR Part 15 Class A
EN 55022	EN 55022 Class A
Approvals	
Safety of industrial control equipment	cUL 508
Safety of information technology equipment	cUL 60950-1
Scope of delivery and accessories	
Scope of delivery	MACH100 device, terminal block for signal contact, 2 brackets with fasteningscrews (pre-assembled), housing feet - stick-on, non-heating appliance cable - Euro model, CD-ROM with user manual, installation user manual
Accessories to order separately	Fast Ethernet SFP modules, Gigabit Ethernet SFP modules, autoConfiguration Adapter ACA21-USB, terminal cable, Industrial Hivision Network Management software

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.



Product information MACH102-8TP-R

Industrial Ethernet:Workgroup Switches:Fast-/Gigabit Ethernet Workgroup Switches, 10/24 ports :MACH102-8TP-R

<http://www.e-catalog.beldensolutions.com/link/57078-24455-49848-85612-40981/en/conf/uislate>

Name	MACH102-8TP-R
	
	26 port Fast Ethernet/Gigabit Ethernet Industrial Workgroup Switch (fix installed: 2 x GE, 8 x FE; via Media Modules 16 x FE), managed, Software Layer 2 Professional, Store-and-Forward-Switching, fanless Design, redundant power supply
Delivery informations	
Availability	available
Product description	
Description	26 port Fast Ethernet/Gigabit Ethernet Industrial Workgroup Switch (fix installed: 2 x GE, 8 x FE; via Media Modules 16 x FE), managed, Software Layer 2 Professional, Store-and-Forward-Switching, fanless Design, redundant power supply
Port type and quantity	Up to 26 Ethernet ports, thereof up to 16 Fast-Ethernet ports via media modules realisable; 8x TP (10/100 BASE-TX, RJ45) Fast Ethernet ports and 2 Gigabit Combo ports fix installed
Type	MACH102-8TP-R
Order No.	943 969-101
More interfaces	
Power supply/signaling contact	1 x plug-in terminal block, 2-pin, output manual or automatic switchable (max. 1 A, 24 V DC bzw. 24 V AC)
V.24 interface	1 x RJ11 socket, serial interface for device configuration
USB interface	1 x to connect auto-configuration adapter ACA21-USB
Network size - length of cable	
Twisted pair (TP)	0 - 100m
Multimode fiber (MM) 50/125 µm	Fast Ethernet: cf. SFP LWL module M-FAST SFP-MM/LC; Gigabit Ethernet: cf. SFP LWL module M-SFP-SX/LC and M-SFP-LX/LC
Multimode fiber (MM) 62.5/125 µm	Fast Ethernet: cf. SFP LWL module M-FAST SFP-MM/LC; Gigabit Ethernet: cf. SFP LWL module M-SFP-SX/LC and M-SFP-LX/LC
Single mode fiber (SM) 9/125 µm	Fast Ethernet: cf. SFP LWL module M-FAST SFP-SM/LC and M-FAST SFP-SM+/LC; Gigabit Ethernet: cf. SFP LWL module M-SFP-LX/LC
Single mode fiber (LH) 9/125 µm (long haul transceiver)	Fast Ethernet: cf. SFP LWL modul M-FAST SFP-LH/LC; Gigabit Ethernet: cf. SFP LWL modul M-SFP-LH/LC and M-SFP-LH+/LC
Network size - cascading	
Line - / star topology	any
Ring structure (HIPER-Ring) quantity switches	50 (reconfiguration time < 0,3 sec.)
Power requirements	
Operating voltage	100 - 240 VAC, 47 - 63 Hz (redundant)
Power output in Btu (IT) h	44 (without media modules)
Rated current	0.4 - 0.2 A
Power consumption	13 W (without media modules)
Software	
Management	serial Interface, web interface, SNMP V1/V2, HiVision file transfer SW HTTP/TFTP, LLDP-MED
Diagnostics	LEDs, log-file, syslog, relay contact, RMON, port mirroring 1:1 and n:1, egress/ingress traffic configurable, topology discovery 802.1AB, cable tester (TX), address conflict detection, network error detection, SFP diagnostic [temperature, optical input and output power (µW and dBm)], Trap for configuration saving and changing, duplex mismatch detection, disable learning, Port Monitor
Configuration	Comand line interface (CLI), TELNET, BootP, DHCP, DHCP option 82, HIDiscovery, easy device exchange with auto-configuration adapter ACA21-USB (automatic software and/or configuration upload), automatic script load from ACA21, integrated DHCP server per port, DHCP relay, automatic invalid configuration undo, Offline Configuration, SFP Whitelist, ARC automatic ring configuration (MRP), automatic port shutdown (link flapping), configuration signature (water marking), overload detection
Security	ACL/QoS, ACL Layer 4 fragment support, Port Security (IP und MAC) with multiple addresses (MAC 50 per port), SNMP V3, SSH, Authentication (IEEE802.1x), 802.1x Multi Client Authentication, Guest VLAN and Unauthenticated VLAN, Port based Radius VLAN assignment, MAC notification
Redundancy functions	HIPER-Ring, MRP, MSTP, RSTP - IEEE802.1D-2004, MRP and RSTP gleichzeitig, Link Aggregation, redundant 100 - 240 VAC power supply
Filter	QoS 8 classes, prioritisation (IEEE 802.1D/p), VLAN (IEEE 802.1Q), Voice VLAN, shared VLAN learning, Q-in-Q double VLAN tagging, multicast IGMP v1/v2/v3, (snooping/querier), multicast detection unknown multicast, broadcast-, unicast-, multicast limiter, fast aging, GMRP IEEE 802.1D, Jumbo Frame Support,

Industrial Ethernet: Workgroup Switches: Fast-/Gigabit Ethernet Workgroup Switches, 10/24 ports :MACH102-8TP-R
<http://www.e-catalog.beldensolutions.com/link/57078-24455-49848-85612-40981/en/conf/ui/state>

	Industrial Profiles, EtherNet/IP und PROFINET (2.2 PDEV, GSDML Stand-alone generator, automatic device exchange) profiles included, configuration and diagnostic via automation, software tools like e.g. STEP7, oder Control Logix IEC61850 protocol (MMS Server, Switch Model)
Industrial Profiles	EtherNet/IP, PROFINET, configuration and diagnostic via automation software tools like e.g. STEP7, or Control Logix
Time synchronisation	PTP IEEE 1588 v1/v2 Boundary and Transparent Clock hardware time stamping with accuracies of 30ns, SNTP server, realtime clock with energy buffer
Flow control	Flow Control 802.3x, Port Priority 802.1D/p, Priority (TOS/DIFFSERV), Prio (MAC/IP), Prio Mapping (TOS Layer2), Traffic Shaping (Unicast, Multicast, Broadcast) Ingress / Egress
Ambient conditions	
Operating temperature	0° - +50°C
Storage/transport temperature	-20° - +85°C
Relative humidity (non-condensing)	10% to 95%
MTBF	18.06 years (MIL-HDBK-217F Gb 25°C) (without media modules)
Mechanical construction	
Dimensions (W x H x D)	448 x 44 x 310 (without fixing bracket)
Mounting	19" control cabinet
Weight	3.85 kg
Protection class	IP20
EMC interference immunity	
EN 61000-4-2 electrostatic discharge (ESD)	4 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80 - 2700 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 4 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 4 kV data line
EN 61000-4-6 conducted immunity	10 V (150 kHz - 80 MHz)
EMC emitted immunity	
FCC CFR47 Part 15	FCC 47 CFR Part 15 Class A
EN 55022	EN 55022 Class A
Approvals	
Safety of industrial control equipment	cUL 508
Safety of information technology equipment	cUL 60950-1
Scope of delivery and accessories	
Scope of delivery	MACH100 device, terminal block for signal contact, 2 brackets with fasteningscrews (pre-assembled), housing feet - stick-on, non-heating appliance cable - Euro model, CD-ROM with user manual, installation user manual
Accessories to order separately	Fast Ethernet SFP modules, Gigabit Ethernet SFP modules, autoConfiguration Adapter ACA21-USB, terminal cable, Industrial Hivision Network Management software

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

 E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.



Product information MACH102-8TP

Industrial Ethernet:Workgroup Switches:Fast-/Gigabit Ethernet Workgroup Switches, 10/24 ports :MACH102-8TP

<http://www.e-catalog.beldensolutions.com/link/57078-24455-49848-85612-40982/en/conf/uisstate>

Name	MACH102-8TP
	
	26 port Fast Ethernet/Gigabit Ethernet Industrial Workgroup Switch (fix installed: 2 x GE, 8 x FE; via Media Modules 16 x FE), managed, Software Layer 2 Professional, Store-and-Forward-Switching, fanless Design
Delivery informations	
Availability	available
Product description	
Description	26 port Fast Ethernet/Gigabit Ethernet Industrial Workgroup Switch (fix installed: 2 x GE, 8 x FE; via Media Modules 16 x FE), managed, Software Layer 2 Professional, Store-and-Forward-Switching, fanless Design
Port type and quantity	Up to 26 Ethernet ports, thereof up to 16 Fast-Ethernet ports via media modules realisable; 8x TP (10/100 BASE-TX, RJ45) Fast Ethernet ports and 2 Gigabit Combo ports fix installed
Type	MACH102-8TP
Order No.	943 969-001
More interfaces	
Power supply/signaling contact	1 x plug-in terminal block, 2-pin, output manual or automatic switchable (max. 1 A, 24 V DC bzw. 24 V AC)
V.24 interface	1 x RJ11 socket, serial interface for device configuration
USB interface	1 x to connect auto-configuration adapter ACA21-USB
Network size - length of cable	
Twisted pair (TP)	0 - 100m
Multimode fiber (MM) 50/125 µm	Fast Ethernet: cf. SFP LWL module M-FAST SFP-MM/LC; Gigabit Ethernet: cf. SFP LWL module M-SFP-SX/LC and M-SFP-LX/LC
Multimode fiber (MM) 62.5/125 µm	Fast Ethernet: cf. SFP LWL module M-FAST SFP-MM/LC; Gigabit Ethernet: cf. SFP LWL module M-SFP-SX/LC and M-SFP-LX/LC
Single mode fiber (SM) 9/125 µm	Fast Ethernet: cf. SFP LWL module M-FAST SFP-SM/LC and M-FAST SFP-SM+/LC; Gigabit Ethernet: cf. SFP LWL module M-SFP-LX/LC
Single mode fiber (LH) 9/125 µm (long haul transceiver)	Fast Ethernet: cf. SFP LWL modul M-FAST SFP-LH/LC; Gigabit Ethernet: cf. SFP LWL modul M-SFP-LH/LC and M-SFP-LH+/LC
Network size - cascadiability	
Line - / star topology	any
Ring structure (HIPER-Ring) quantity switches	50 (reconfiguration time < 0,3 sec.)
Power requirements	
Operating voltage	100 - 240 VAC, 47 - 63 Hz
Power output in Btu (IT) h	41 (without media modules)
Rated current	0.4 - 0.2 A
Power consumption	12 W (without media modules)
Software	
Management	serial Interface, web interface, SNMP V1/V2, HiVision file transfer SW HTTP/TFTP, LLDP-MED
Diagnostics	LEDs, log-file, syslog, relay contact, RMON, port mirroring 1:1 and n:1, egress/ingress traffic configurable, topology discovery 802.1AB, cable tester (TX), address conflict detection, network error detection, SFP diagnostic [temperature, optical input and output power (µW and dBm)], Trap for configuration saving and changing, duplex mismatch detection, disable learning, Port Monitor
Configuration	Comand line interface (CLI), TELNET, BootP, DHCP, DHCP option 82, HIDiscovery, easy device exchange with auto-configuration adapter ACA21-USB (automatic software and/or configuration upload), automatic script load from ACA21, integrated DHCP server per port, DHCP relay, automatic invalid configuration undo, Offline Configuration, SFP Whitelist, ARC automatic ring configuration (MRP), automatic port shutdown (link flapping), configuration signature (water marking), overload detection
Security	ACL/QoS, ACL Layer 4 fragment support, Port Security (IP und MAC) with multiple addresses (MAC 50 per port), SNMP V3, SSH, Authentication (IEEE802.1x), 802.1x Multi Cliaint Authentication, Guest VLAN and Unauthenticated VLAN, Port based Radius VLAN assignment, MAC notification
Redundancy functions	HIPER-Ring, MRP, MSTP, RSTP - IEEE802.1D-2004, MRP and RSTP gleichzeitig, Link Aggregation, dual homing, link aggregation
Filter	QoS 8 classes, prioritisation (IEEE 802.1D/p), VLAN (IEEE 802.1Q), Voice VLAN, shared VLAN learning, Q-in-Q double VLAN tagging, multicast IGMP v1/v2/v3, (snooping/querier), multicast detection unknown multicast, broadcast-, unicast-, multicast limiter, fast aging, GMRP IEEE 802.1D, Jumbo Frame Support,

Industrial Ethernet: Workgroup Switches: Fast-/Gigabit Ethernet Workgroup Switches, 10/24 ports :MACH102-8TP
<http://www.e-catalog.beldensolutions.com/link/57078-24455-49848-85612-40982/en/conf/ui/state>

	Industrial Profiles, EtherNet/IP und PROFINET (2.2 PDEV, GSDML Stand-alone generator, automatic device exchange) profiles included, configuration and diagnostic via automation, software tools like e.g. STEP7, oder Control Logix IEC61850 protocol (MMS Server, Switch Model)
Industrial Profiles	EtherNet/IP, PROFINET, configuration and diagnostic via automation software tools like e.g. STEP7, or Control Logix
Time synchronisation	PTP IEEE 1588 v1/v2 Boundary and Transparent Clock hardware time stamping with accuracies of 30ns, SNTP server, realtime clock with energy buffer
Flow control	Flow Control 802.3x, Port Priority 802.1D/p, Priority (TOS/DIFFSERV), Prio (MAC/IP), Prio Mapping (TOS Layer2), Traffic Shaping (Unicast, Multicast, Broadcast) Ingress / Egress
Ambient conditions	
Operating temperature	0° - +50°C
Storage/transport temperature	-20° - +85°C
Relative humidity (non-condensing)	10% to 95%
MTBF	15.67 years (MIL-HDBK-217F Gb 25°C) (without media modules)
Mechanical construction	
Dimensions (W x H x D)	448 x 44 x 310 (without fixing bracket)
Mounting	19" control cabinet
Weight	3.60 kg
Protection class	IP20
EMC interference immunity	
EN 61000-4-2 electrostatic discharge (ESD)	4 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80 - 2700 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 4 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 4 kV data line
EN 61000-4-6 conducted immunity	10 V (150 kHz - 80 MHz)
EMC emitted immunity	
FCC CFR47 Part 15	FCC 47 CFR Part 15 Class A
EN 55022	EN 55022 Class A
Approvals	
Safety of industrial control equipment	cUL 508
Safety of information technology equipment	cUL 60950-1
Scope of delivery and accessories	
Scope of delivery	MACH100 device, terminal block for signal contact, 2 brackets with fasteningscrews (pre-assembled), housing feet - stick-on, non-heating appliance cable - Euro model, CD-ROM with user manual, installation user manual
Accessories to order separately	Fast Ethernet SFP modules, Gigabit Ethernet SFP modules, autoConfiguration Adapter ACA21-USB, terminal cable, Industrial Hivision Network Management software

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.



Product information MACH102-24TP-FR

Industrial Ethernet:Workgroup Switches:Fast-/Gigabit Ethernet Workgroup Switches, 10/24 ports :MACH102-24TP-FR

<http://www.e-catalog.beldensolutions.com/link/57078-24455-49848-85612-40983/en/conf/uisstate>

Name	MACH102-24TP-FR
	
	26 port Fast Ethernet/Gigabit Ethernet Industrial Workgroup Switch (2 x GE, 24 x FE), managed, Software Layer 2 Professional, Store-and-Forward-Switching, fanless Design, redundant power supply
Delivery informations	
Availability	available
Product description	
Description	26 port Fast Ethernet/Gigabit Ethernet Industrial Workgroup Switch (2 x GE, 24 x FE), managed, Software Layer 2 Professional, Store-and-Forward-Switching, fanless Design, redundant power supply
Port type and quantity	26 ports in total; 24x (10/100 BASE-TX, RJ45) and 2 Gigabit Combo ports
Type	MACH102-24TP-FR
Order No.	943 969-501
More Interfaces	
Power supply/signaling contact	1 x plug-in terminal block, 2-pin, output manual or automatic switchable (max. 1 A, 24 V DC bzw. 24 V AC)
V.24 interface	1 x RJ11 socket, serial interface for device configuration
USB interface	1 x to connect auto-configuration adapter ACA21-USB
Network size - length of cable	
Twisted pair (TP)	0 - 100m
Multimode fiber (MM) 50/125 µm	Fast Ethernet: cf. SFP LWL module M-FAST SFP-MM/LC; Gigabit Ethernet: cf. SFP LWL module M-SFP-SX/LC and M-SFP-LX/LC
Multimode fiber (MM) 62.5/125 µm	Fast Ethernet: cf. SFP LWL module M-FAST SFP-MM/LC; Gigabit Ethernet: cf. SFP LWL module M-SFP-SX/LC and M-SFP-LX/LC
Single mode fiber (SM) 9/125 µm	Fast Ethernet: cf. SFP LWL module M-FAST SFP-SM/LC and M-FAST SFP-SM+/LC; Gigabit Ethernet: cf. SFP LWL module M-SFP-LX/LC
Single mode fiber (LH) 9/125 µm (long haul transceiver)	Fast Ethernet: cf. SFP LWL modul M-FAST SFP-LH/LC; Gigabit Ethernet: cf. SFP LWL modul M-SFP-LH/LC and M-SFP-LH+/LC
Network size - cascadiability	
Line - / star topology	any
Ring structure (HIPER-Ring) quantity switches	50 (reconfiguration time < 0,3 sec.)
Power requirements	
Operating voltage	100 - 240 VAC, 47 - 63 Hz (redundant)
Power output in Btu (IT) h	58
Rated current	0.4 - 0.2 A
Power consumption	17 W
Software	
Management	serial Interface, web interface, SNMP V1/V2, HiVision file transfer SW HTTP/TFTP, LLDP-MED
Diagnostics	LEDs, log-file, syslog, relay contact, RMON, port mirroring 1:1 and n:1, egress/ingress traffic configurable, topology discovery 802.1AB, cable tester (TX), address conflict detection, network error detection, SFP diagnostic [temperature, optical input and output power (µW and dBm)], Trap for configuration saving and changing, duplex mismatch detection, disable learning, Port Monitor
Configuration	Comand line interface (CLI), TELNET, BootP, DHCP, DHCP option 82, HiDiscovery, auto-configuration adapter (ACD11, ACA21-USB), Watchdog configuration; integrated DHCP server
Security	Port security (IP and MAC), SNMP V3, SSH, authentication (802.1x)
Redundancy functions	HIPER-ring (ring structure), MRP (IEC-ring functionality), RSTP 802.1D-2004, redundant network/ring coupling, dual homing, link aggregation, redundant 100 - 240 VAC power supply
Filter	QoS 4 Klassen, Portpriorisierung (IEEE 802.1D/p), VLAN (IEEE 802.1Q), shared VLAN learning, Multicast (IGMP Snooping/Querier), Multicast Detection unknown Multicast, Broadcastlimiter, Fast Aging, Multicast GMRP IEEE 802.1D
Industrial Profiles	EtherNet/IP, PROFINET, configuration and diagnostic via automation software tools like e.g. STEP7, or Control Logix
Time synchronisation	SNTP server, realtime clock with energy buffer
Flow control	Flow Control 802.3x, Port Priority 802.1D/p, Priority (TOS/DIFFSERV), Prio (MAC/IP), Prio Mapping (TOS Layer2), Traffic Shaping (Unicast, Multicast, Broadcast) Ingress / Egress



Industrial Ethernet:Workgroup Switches:Fast-/Gigabit Ethernet Workgroup Switches, 10/24 ports :MACH102-24TP-FR

<http://www.e-catalog.beldensolutions.com/link/57078-24455-49848-85612-40983/en/conf/ui/state>

Ambient conditions

Operating temperature	0° - +50°C
Storage/transport temperature	-20° - +85°C
Relative humidity (non-condensing)	10% to 95%
MTBF	14.93 years (MIL-HDBK-217F Gb 25°C)

Mechanical construction

Dimensions (W x H x D)	448 x 44 x 310 (without fixing bracket)
Mounting	19" control cabinet
Weight	4.10 kg
Protection class	IP20

EMC interference immunity

EN 61000-4-2 electrostatic discharge (ESD)	4 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80 - 2700 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 4 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 4 kV data line
EN 61000-4-6 conducted immunity	10 V (150 kHz - 80 MHz)

EMC emitted immunity

FCC CFR47 Part 15	FCC 47 CFR Part 15 Class A
EN 55022	EN 55022 Class A

Approvals

Safety of industrial control equipment	cUL 508
Safety of information technology equipment	cUL 60950-1

Scope of delivery and accessories

Scope of delivery	MACH100 device, terminal block for signal contact, 2 brackets with fasteningscrews (pre-assembled), housing feet - stick-on, non-heating appliance cable - Euro model, CD-ROM with user manual, installation user manual
Accessories to order separately	Fast Ethernet SFP modules, Gigabit Ethernet SFP modules, autoConfiguration Adapter ACA21-USB, terminal cable, Industrial Hivision Network Management software

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51
72654 Neckartenzlingen
Germany
Phone: +49 7127/14-1809
E-Mail: inet-sales@belden.com


The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.



Product information MACH102-24TP-F

Industrial Ethernet:Workgroup Switches:Fast-/Gigabit Ethernet Workgroup Switches, 10/24 ports :MACH102-24TP-F

<http://www.e-catalog.beldensolutions.com/link/57078-24455-49848-85612-40984/en/conf/uisstate>

Name	MACH102-24TP-F
	
	26 port Fast Ethernet/Gigabit Ethernet Industrial Workgroup Switch (2 x GE, 24 x FE), managed, Software Layer 2 Professional, Store-and-Forward-Switching, fanless Design
Delivery informations	
Availability	available
Product description	
Description	26 port Fast Ethernet/Gigabit Ethernet Industrial Workgroup Switch (2 x GE, 24 x FE), managed, Software Layer 2 Professional, Store-and-Forward-Switching, fanless Design
Port type and quantity	26 ports in total; 24x (10/100 BASE-TX, RJ45) and 2 Gigabit Combo ports
Type	MACH102-24TP-F
Order No.	943 969-401
More Interfaces	
Power supply/signaling contact	1 x plug-in terminal block, 2-pin, output manual or automatic switchable (max. 1 A, 24 V DC bzw. 24 V AC)
V.24 interface	1 x RJ11 socket, serial interface for device configuration
USB interface	1 x to connect auto-configuration adapter ACA21-USB
Network size - length of cable	
Twisted pair (TP)	0 - 100m
Multimode fiber (MM) 50/125 µm	Fast Ethernet: cf. SFP LWL module M-FAST SFP-MM/LC; Gigabit Ethernet: cf. SFP LWL module M-SFP-SX/LC and M-SFP-LX/LC
Multimode fiber (MM) 62.5/125 µm	Fast Ethernet: cf. SFP LWL module M-FAST SFP-MM/LC; Gigabit Ethernet: cf. SFP LWL module M-SFP-SX/LC and M-SFP-LX/LC
Single mode fiber (SM) 9/125 µm	Fast Ethernet: cf. SFP LWL module M-FAST SFP-SM/LC and M-FAST SFP-SM+/LC; Gigabit Ethernet: cf. SFP LWL module M-SFP-LX/LC
Single mode fiber (LH) 9/125 µm (long haul transceiver)	Fast Ethernet: cf. SFP LWL modul M-FAST SFP-LH/LC; Gigabit Ethernet: cf. SFP LWL modul M-SFP-LH/LC and M-SFP-LH+/LC
Network size - cascading	
Line - / star topology	any
Ring structure (HIPER-Ring) quantity switches	50 (reconfiguration time < 0,3 sec.)
Power requirements	
Operating voltage	100 - 240 VAC, 47 - 63 Hz
Power output in Btu (IT) h	55
Rated current	0.4 - 0.2 A
Power consumption	16 W
Software	
Management	serial Interface, web interface, SNMP V1/V2, HiVision file transfer SW HTTP/TFTP, LLDP-MED
Diagnostics	LEDs, log-file, syslog, relay contact, RMON, port mirroring 1:1 and n:1, egress/ingress traffic configurable, topology discovery 802.1AB, cable tester (TX), address conflict detection, network error detection, SFP diagnostic [temperature, optical input and output power (µW and dBm)], Trap for configuration saving and changing, duplex mismatch detection, disable learning, Port Monitor
Configuration	Comand line interface (CLI), TELNET, BootP, DHCP, DHCP option 82, HiDiscovery, easy device exchange with auto-configuration adapter ACA21-USB (automatic software and/or configuration upload), automatic script load from ACA21, integrated DHCP server per port, DHCP relay, automatic invalid configuration undo, Offline Configuration, SFP Whitelist, ARC automatic ring configuration (MRP), automatic port shutdown (link flapping), configuration signature (water marking), overload detection
Security	ACL/QoS, ACL Layer 4 fragment support, Port Security (IP und MAC) with multiple addresses (MAC 50 per port), SNMP V3, SSH, Authentication (IEEE802.1x), 802.1x Multi Client Authentication, Guest VLAN and Unauthenticated VLAN, Port based Radius VLAN assignment, MAC notification
Redundancy functions	HIPER-Ring, MRP, MSTP, RSTP - IEEE802.1D-2004, MRP and RSTP gleichzeitig, Link Aggregation
Filter	QoS 8 classes, prioritisation (IEEE 802.1D/p), VLAN (IEEE 802.1Q), Voice VLAN, shared VLAN learning, Q-in-Q double VLAN tagging, multicast IGMP v1/v2/v3, (snoothing/querier), multicast detection unknown multicast, broadcast-, unicast-, multicast limiter, fast aging, GMRP IEEE 802.1D, Jumbo Frame Support, Industrial Profiles, EtherNet/IP und PROFINET (2.2 PDEV, GSDML Stand-alone generator, automatic device exchange) profiles included, configuration and diagnostic via automation, software tools like e.g. STEP7, oder Control Logix IEC61850 protocol (MMS Server, Switch Model)



Industrial Ethernet:Workgroup Switches:Fast-/Gigabit Ethernet Workgroup Switches, 10/24 ports :MACH102-24TP-F

<http://www.e-catalog.beldensolutions.com/link/57078-24455-49848-85612-40984/en/conf/ui/istate>

Industrial Profiles	EtherNet/IP, PROFINET, configuration and diagnostic via automation software tools like e.g. STEP7, or Control Logix
Time synchronisation	PTP IEEE 1588 v1/v2 Boundary and Transparent Clock hardware time stamping with accuracies of 30ns, SNTP server, realtime clock with energy buffer
Flow control	Flow Control 802.3x, Port Priority 802.1D/p, Priority (TOS/DIFFSERV), Prio (MAC/IP), Prio Mapping (TOS Layer2), Traffic Shaping (Unicast, Multicast, Broadcast) Ingress / Egress
Ambient conditions	
Operating temperature	0° - +50°C
Storage/transport temperature	-20° - +85°C
Relative humidity (non-condensing)	10% to 95%
MTBF	13.26 years (MIL-HDBK-217F Gb 25°C)
Mechanical construction	
Dimensions (W x H x D)	448 x 44 x 310 (without fixing bracket)
Mounting	19" control cabinet
Weight	3.85 kg
Protection class	IP20
EMC interference immunity	
EN 61000-4-2 electrostatic discharge (ESD)	4 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80 - 2700 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 4 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 4 kV data line
EN 61000-4-6 conducted immunity	10 V (150 kHz - 80 MHz)
EMC emitted immunity	
FCC CFR47 Part 15	FCC 47 CFR Part 15 Class A
EN 55022	EN 55022 Class A
Approvals	
Safety of industrial control equipment	cUL 508
Safety of information technology equipment	cUL 60950-1
Scope of delivery and accessories	
Scope of delivery	MACH100 device, terminal block for signal contact, 2 brackets with fasteningscrews (pre-assembled), housing feet - stick-on, non-heating appliance cable - Euro model, CD-ROM with user manual, installation user manual
Accessories to order separately	Fast Ethernet SFP modules, Gigabit Ethernet SFP modules, autoConfiguration Adapter ACA21-USB, terminal cable, Industrial Hivision Network Management software

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.