



**TEKRON**  
INTERNATIONAL

## GPS NETWORK TIME SERVER NTS 01



### NTS 01 – GPS Network Time Server

- An economic network time synchronization solution with excellent timing accuracy (to within 1 millisecond of UTC).
- Designed for synchronizing industrial control and SCADA networks.
- Provides NTP/SNTP Network Time Server function, featuring DHCP or programmable fixed IP address, SNMP supervision.
- Offers UTP network interfaces for functioning as a Stratum 1 Time Server.
- Available with either 2 or 5 ports, each port functions as an NTP Time Server.

[www.tekroninternational.com](http://www.tekroninternational.com)

409 Cuba Street, Aicetown  
PO Box 31 285, Lower Hutt 6009, New Zealand  
Phone: +64 4 566 7722, Fax: +64 4 569 9272

**TEKRON**  
INTERNATIONAL

## SPECIFICATIONS

---

### NTS 01 – GPS Network Time Server

#### Physical

- Antenna: 80mm diameter x 60mm high cone.
- NTS 01 unit:
  - 1U 19" rackmount
  - 160mm wide x 40mm high x 160mm deep
  - Display LCD 2 line x 16 char

#### Outputs

##### NTS 01

- 2 RJ45 UTP connectors
- 10Mbs Ethernet port (10 baseT)
- Each port has a unique programmable IP address

##### Expansion Unit (Optional)

- 3 RJ45 UTP connectors
- 10Mbs Ethernet port (10 baseT)
- Each port has a unique programmable IP address

#### Protocols supported:

- ARP, TCP, ICMP, Telnet, TFTP, DHCP, SNMP and BOOTP

#### Client protocols supported:

- NTP/SNTP

#### Power Supply

##### Range Options:

L = 12-36Vdc

M = 20-72Vdc

H = 90-300Vdc

240Vac-24Vdc GPO plug pack

Power Drain: 3W max (dependent on load attached)

#### Environmental

##### Antenna:

Operating temperature: -40°C to +85°C  
Humidity: To 100%

##### NTS01 unit:

Operating temperature: -10°C to +65°C  
Humidity: 95% non condensing

#### Accuracy

- Output accurate to within 1 millisecond of UTC when 4 or more satellites being tracked.

#### NTS 01 Kit Contents

- GPS antenna
- 15m length antenna cable (see options below)
- NTS 01 unit
- 1U 19" rackmount
- 2m CAT5e UTP drop lead
- Configuration s/w and USB cable
- User manual

#### Options

- *Lightning Protection Kit*

Includes protector unit plus cable connectors, tool for installation, and instructions – also available as a separately orderable item.

- *Optional Expansion Unit (3 UTP ports)*

- *Antenna cable options:*

Standard: 15m (50ft) antenna cable  
Opt 30m: 30m (100ft) antenna cable  
Opt 60m: 60m (200ft) antenna cable

All specifications subject to change without notice

---

[www.tekroninternational.com](http://www.tekroninternational.com)

409 Cuba Street, Aicetown  
PO Box 31 285, Lower Hutt 6009, New Zealand  
Phone: +64 4 566 7722, Fax: +64 4 569 9272

**TEKRON**  
INTERNATIONAL