

Solar Charge Controller for Solar Home System

SNI: 04-6391-2000
Electronic Fuse
1 Years Warranty



Temperature Compensated
Overcharge Protection
Proof Against Operating Errors
Over discharge Protection
Overvoltage Protection
LED – Voltage Display
12 / 24 Volt DC System
Efficiency >92%

Integrated with:
Switch for three lamp
DC outlet 12 VDC
Cable for Battery Connection
3 Lamp terminals

Technical Data :

Type	SCRU 10.10 F
Jenis	On-Off Seri / PWM
Tegangan Nominal	12 Vdc
Rating Arus Input	8 A
Rating Arus beban	10 A
Tegangan batas atas	14.50 V
Tegangan Rekomendasi batas atas	13.70 V
Tegangan batas bawah	11.50 V
Tegangan Rekomendasi batas bawah	12.50 V
Short Circuit Protection	Electronic
Terminal Output	6V, 9V, 12V
Dimensi (L x W x D)	200 x 110 x 48 mm
Garansi	1 tahun
Sertifikat	SNI 04-6391-2000 dari B2TE yang masih berlaku
Indikator	- pengisian LED menyala warna Hijau - Batttery penuh LED menyala warna Hijau - Batttery hamper kosong LED menyala warna Merah - Terjadi hubung singkat LED menyala Merah

For 24 V System Voltage are to be double