

Teleflex SX

Portable reflectometer for fault location systems



- **ARMslide technology with 15 traces in one ARM shot**
- **ProRange for optimised display of distant details**
- **Support of all existing prelocation technologies**
- **Automatic adjustment and display of cable end and fault**
- **Compatible with all fault location systems**

DESCRIPTION

With the new Teleflex SX the excellent properties of the successful Teleflex VX were transferred into a smaller, handy and portable design. The Teleflex SX is operated by the new touchscreen and the wellproven control knob functionality. The interface is shown on a sharp and very bright 10.4" display.

The Teleflex SX is specially adapted to the fast events during fault location in power cables. The easyGO operation is reduced to the important and essential steps and runs mostly fully automatically.

The new hardware with improved parameters as sampling frequency, pulse width and impulse amplitude guarantees larger ranges and highest resolution.

The touchscreen operation allows an even easier and faster handling, especially in the case of detail data entry as it is required for the reporting menu.

The ΔU Trigger technology provides always perfect trigger in the correct moment.

ARMslide records 15 traces in one shot allowing a selection of the best trace, very helpful for wet and long, difficult cables.

The ProRange function allows a distance adapted gain, displaying far distant events with the same amplitude as from short distances.

Via CAN interface or ethernet, the Teleflex SX can be integrated into a system, which allows the remote control in offshore applications and ROV's.

By the CAN interface, the Teleflex SX becomes the combined control unit of the SPG 40 fault location system, which allows an easy and more intuitive operation of the complete fault location process.

The Linux®-based operating system stands out by highest reliability.

FEATURES AND BENEFITS

- Large 10.4" sunlight-readable colour display
- Easiest operation by touchscreen and control knob
- Support of all existing prelocation technologies
- Automatic trace analysis (cable end and fault position indication)
- Integrated battery
- Top performance
- Compatible with all fault location systems

Functions

- ARMslide with 15 traces per ARM shot
- ProRange technology
- Dual phased reflectometer (TDR) with simultaneous color display of up to 6 traces
- Automatic adjustment and display of cable end and fault
- High resolution by real sample rate of 400 MHz

- Internal compensation for better details at short range
- Large 2 GB memory for automatic storage of all data
- USB interface for data transfer via memory stick and printer
- Control of the SPG 40
- Report generation in *.pdf format

The Teleflex SX supports the following technologies:

- Symmetrical/unsymmetrical reflection measurement
- Difference measurement/comparison
- Two-phase reflection measurement (TDR)
- Optimized support of all Arc reflection methods by ΔU Trigger
- ICE (impulse current methods)
- IFL (intermittent fault locating)
- DECAY travelling wave method
- ARM burning
- Partial discharge pinpointing

SPECIFICATIONS

Range	20 m ... 160 km @ v/2 = 80 m/ μ s
Pulse width	20 ns ... 10 μ s
Pulse amplitude	5 ... 50 V
Resolution	0,1 m @ v/2 80 m/ μ s, 1,0 cm @ v/2 < 40 m/ μ s
Sample rate	Up to 400 MHz
Gain	- 37 ... +37 db
De-attenuation	0 ... +22dB for ProRange (adjustable 0 ... 100 %)
Propagation velocity V/2	Propagation velocity V/2
Dynamic range	80 dB
Output impedance	50 Ω
Compensation	8 Ω ... 500 Ω , adjustable
ARM trigger	Automatic adaptation by ΔU Trigger.
ARMslide	15 measurements in one ARM shot
Dead zone	None
Voltage proof input	< 400 V, operation only with separation filter
Display	10.4" color TFT XGA 1024x768, touchscreen, 600 cd/m ² , LED-Backlight, dimmable
Data storage	4 GB mSATA for program and data
Connectors	Ethernet, USB, BNC, CAN (LON optional)
Protection class	IP 65 closed, IP 54 open lid
Supply	110 ... 240 V, 50/60 Hz, 30 VA 10 V ... 17 V DC, 3.8 A
Dimensions (W x H x D)	362 x 195 x 306 mm (option 19", 6 HU)
Weight	10 kg
Operation temperature	-10 °C ... +50 °C
Storage temperature	-20 °C ... +60 °C

ORDERING INFORMATION

Item	Cat. No.
Teleflex SX	128312895
available as portable, battery operated stand-alone version but can be integrated in any measuring system with 19" rack mounting	

SEBAKMT
Dr.-Herbert-Iann-Str. 6
96148 Baunach / Germany
T +49 (0) 95 44 6 80
F +49 (0) 95 44 22 73
sales@sebakmt.com

UNITED STATES
4271 Bronze Way
Dallas TX 75237-1019 USA
T 800 723 2861 (USA only)
T +1 214 333 3201
F +1 214 331 7399
USsales@megger.com

OTHER TECHNICAL SALES OFFICES
Dover UK, Valley Forge USA, College Station USA,
Sydney AUSTRALIA, Täby SWEDEN, Ontario
CANADA, Trappes FRANCE, Oberursel GERMANY,
Aargau SWITZERLAND, Kingdom of SAUDI ARABIA,
Mumbai INDIA, Johannesburg SOUTH AFRICA,
Chonburi THAILAND

CERTIFICATION ISO
Registered to ISO 9001:2000 Cert. no. Q 09290
Registered to ISO 14001:1996 Cert. no. EMS 61597
Teleflex_SX_DS_EN_V01US
www.megger.com
Megger is a registered trademark