

***Superior product for  
special locations -  
Less corrosion  
Long Life  
Better Appearance !***



#### 1. High Resistance to Corrosion

Stainless Steel (SUS304) construction *ensures against* rust in corrosive areas, such as food processing lines, chemical plants, water treatment plants, seashore plant, etc.

#### 2. Conforming to IMC conduit

Internal diameter and length *conform to IMC requirement*. Can be combined with steel conduit for a more flexible, reliable wiring installation in a variety of applications. Stainless conduit fittings help form a complete, professional wiring system.

#### 3. Long Lifetime

Conduit system must remain in a good condition wherever they are installed. Stainless steel conduit delivers a long lifetime and *require little maintenance* especially in high altitude installations.

#### 4. Brilliant Appearance

Stainless steel conduit polished to a bright finish for a superior appearance. This ensures an *attractive appearance* of special importance to food processing lines.



**STAINLESS STEEL CONDUIT PIPE (IMC TYPE)**

**Stainless Steel Conduit Pipe with one coupling and one end**



| Size (inch) | Weight (kg/pce) | Product no. | Outside Diameter (mm) | Wall Thickness (mm) | Length (mm) | Bundle (pcs) |
|-------------|-----------------|-------------|-----------------------|---------------------|-------------|--------------|
| 1/2         | 3.08            | DWSM 012    | 21.1                  | 2.1                 | 3.030       | 10           |
| 3/4         | 3.95            | DWSM 034    | 26.4                  | 2.1                 | 3.030       | 10           |
| 1           | 6.56            | DWSM 100    | 33.6                  | 2.8                 | 3.025       | 5            |
| 1 1/4       | 8.39            | DWSM 114    | 42.2                  | 2.8                 | 3.025       | 3            |
| 1 1/2       | 9.69            | DWSM 112    | 48.3                  | 2.8                 | 3.025       | 3            |
| 2           | 12.29           | DWSM 200    | 60.3                  | 2.8                 | 3.025       | 1            |
| 3           | 26.23           | DWSM 300    | 88.9                  | 4.0                 | 3.010       | 1            |
| 4           | 34.12           | DWSM 400    | 114.2                 | 4.0                 | 3.005       | 1            |

**STAINLESS STEEL CONDUIT FITTINGS**



**Coupling**

| Size (inch) | Weight (kg/pce) | Product no. | Inner Packing (pcs) | Outer Box (pcs) |
|-------------|-----------------|-------------|---------------------|-----------------|
| 1/2         | 0.053           | DFSM 11012  | 25                  | 50              |
| 3/4         | 0.068           | DFSM 11034  | 10                  | 20              |
| 1           | 0.119           | DFSM 11100  | 10                  | 20              |
| 1 1/4       | 0.151           | DFSM 11114  | 10                  | 10              |
| 1 1/2       | 0.190           | DFSM 11112  | 5                   | 5               |
| 2           | 0.281           | DFSM 11200  | 3                   | 6               |
| 3           | 0.728           | DFSM 11300  | 5                   | 5               |
| 4           | 1.019           | DFSM 11400  | 5                   | 5               |



**Normal Bend**

| Size (inch) | Weight (kg/pce) | Product no. | Inner Packing (pcs) | Outer Box (pcs) |
|-------------|-----------------|-------------|---------------------|-----------------|
| 1/2         | 0.284           | DFSM 13012  | 1                   | 10              |
| 3/4         | 0.434           | DFSM 13034  | 1                   | 8               |
| 1           | 0.872           | DFSM 13100  | 1                   | 6               |
| 1 1/4       | 1.409           | DFSM 13114  | 1                   | -               |
| 1 1/2       | 1.860           | DFSM 13112  | 1                   | -               |
| 2           | 2.572           | DFSM 13200  | 1                   | -               |
| 3           | 7.419           | DFSM 13300  | 1                   | -               |
| 4           | 13.945          | DFSM 13400  | 1                   | -               |



**Lock Nut**

| Size (inch) | Weight (kg/pce) | Product no. | Inner Packing (pcs) | Outer Box (pcs) |
|-------------|-----------------|-------------|---------------------|-----------------|
| 1/2         | 0.004           | DFSM 12012  | 50                  | -               |
| 3/4         | 0.006           | DFSM 12034  | 50                  | -               |
| 1           | 0.013           | DFSM 12100  | 50                  | -               |
| 1 1/4       | 0.018           | DFSM 12114  | 50                  | -               |
| 1 1/2       | 0.022           | DFSM 12112  | 30                  | -               |
| 2           | 0.029           | DFSM 12200  | 30                  | -               |
| 3           | 0.063           | DFSM 12300  | 10                  | -               |
| 4           | 0.076           | DFSM 12400  | 10                  | -               |



**Saddle**

| Size (inch) | Weight (kg/pce) | Product no. | Inner Packing (pcs) | Outer Box (pcs) |
|-------------|-----------------|-------------|---------------------|-----------------|
| 1/2         | 0.011           | DFSM 13012  | 25                  | -               |
| 3/4         | 0.013           | DFSM 13034  | 25                  | -               |
| 1           | 0.025           | DFSM 13100  | 25                  | -               |
| 1 1/4       | 0.028           | DFSM 13114  | 25                  | -               |
| 1 1/2       | 0.045           | DFSM 13112  | 15                  | -               |
| 2           | 0.055           | DFSM 13200  | 5                   | -               |
| 3           | 0.113           | DFSM 13300  | 5                   | -               |
| 4           | 0.140           | DFSM 13400  | 5                   | -               |